



half round ridge tiles on 15mm finished mortar bed

2no. extract fan roof outlets, ducts to form condensation trap
Boiler manufacturer's proprietary pitched roof flue terminals

Milbank Roofs Unipur PB self-supporting roof panel system.
Panels 820mm wide.
Type ref PB150/170 183mm thick overall

1no. 778h x 550w Velux rooflight ref GGL C02

twin boiler flues

intermediate purlins

1no. 778h x 550w Velux rooflight ref GGL C02

Forticrete Gemini interlocking concrete tiles on
pre-treated battens at 175mm centres on
a proprietary breathable roofing felt

65mm mesh reinforced cement/sand screed on
separating layer on
65mm flooring grade insulation on
DPM on
beam & block floor system

Rev F: Sept 04 - Roof purlin amended + bathroom extract fans indicated
Rev E: Sept 04 - Velux to single storey amended
Rev D: Aug 04 - roof covering co-ordinated with details
Rev C: Aug 04 - intermediate purlin amended
Rev B: July 04 - co-ordinated with struct. eng. drwgs
Rev A: July 04 - window dimensions amended

<p>SOUTH BANK ARCHITECTS 28A LOWER MARSH LONDON SE1 7RG tel: 020 7928 6144 fax: 020 7620 1966 email: sbarchitects@btconnect.com</p>	
<p><i>client</i></p> <p>DORIC SECURITIES LTD. "Riverside", Wandale Trading Estate, Mitcham, Surrey CR4 4JW</p>	
<p><i>project</i></p> <p>WOOD AVENUE, PURFLEET THURROCK, ESSEX</p>	
<p><i>title</i></p> <p>HOUSES 1 - 4: SECTION AA</p>	
<p><i>scale</i></p> <p>1:25</p>	<p><i>drawing no.</i></p> <p>S1729/411F</p>